

Data Sheet

Shoe Inn

www.ShoeInnShoeCovers.com

1482 Linda Way





toll-free: 877.595.7463

Sparks, NV 89431

fax: 775.358.0736

Fabric Shoe Covers w/ Traction & ESD (7FWT-100HC-ESD)

Shoe Cover Refills for Shoe Inn Fusion and Stay Automatic Shoe Cover Dispensers

Description	Cartridge: 100 Shoe Covers (50 pairs)	
<p>Lightweight, breathable nonwoven fabric shoe cover with traction and an ESD dissipative ribbon with a surface resistance between 3.5×10^7 to 1.0×10^9 ohms. Elastic band around ankle allows for a one-size-fits-most fit. Cleanroom validated.</p>		
Applications (not an exhaustive list)	Shoe Cover Dimensions: 5.5" h x 14" l	
High-Tech		
Electronics Manufacturing		
Data Centers		
Cleanrooms		
Research & Development		
Features	Case: 1,500 Shoe Covers (750 pairs; 15 cartridges)	
Lightweight & breathable		
ESD dissipative		
Traction		
Physical Characteristics	Certifications	
Spunbond polypropylene (28 grams/m ²)	<p>Approved for use in cleanrooms up to Class 100/Class 5 per Fed. STD. 209E/ISO STD. 14644-1, as certified by Ultraclean Products Approval Laboratory. ANSI/ESD S20.20-2014 and ESD SP9.2-2003.</p>	
Traction Pattern: 100% latex (1.2 grams/m ²)		
ESD surface resistance: 3.5×10^7 to 1.0×10^9 ohms		